

Watch Gasket



14.5 X 0.4	15 X 0.4	15.5 X 0.4	16 X 0.4	16.5 X 0.4	17 X 0.4
17.5 X 0.4	18 X 0.4	18.5 X 0.4	19 X 0.4	19.5 X 0.4	20 X 0.4
20.5 X 0.4	21 X 0.4	21.5 X 0.4	22 X 0.4	22.5 X 0.4	23 X 0.4
23.5 X 0.4	24 X 0.4	24.5 X 0.4	25 X 0.4	25.5 X 0.4	26 X 0.4
26.5 X 0.4	27 X 0.4	27.5 X 0.4	28 X 0.4	28.5 X 0.4	29 X 0.4
29.5 X 0.4	30 X 0.4	30.5 X 0.4	31 X 0.4	31.5 X 0.4	32 X 0.4

14.5 X 0.5	15 X 0.5	15.5 X 0.5	16 X 0.5	16.5 X 0.5	17 X 0.5
17.5 X 0.5	18 X 0.5	18.5 X 0.5	19 X 0.5	19.5 X 0.5	20 X 0.5
20.5 X 0.5	21 X 0.5	21.5 X 0.5	22 X 0.5	22.5 X 0.5	23 X 0.5
23.5 X 0.5	24 X 0.5	24.5 X 0.5	25 X 0.5	25.5 X 0.5	26 X 0.5
26.5 X 0.5	27 X 0.5	27.5 X 0.5	28 X 0.5	28.5 X 0.5	29 X 0.5
29.5 X 0.5	30 X 0.5	30.5 X 0.5	31 X 0.5	31.5 X 0.5	32 X 0.5

14.5 X 0.6	15 X 0.6	15.5 X 0.6	16 X 0.6	16.5 X 0.6	17 X 0.6
17.5 X 0.6	18 X 0.6	18.5 X 0.6	19 X 0.6	19.5 X 0.6	20 X 0.6
20.5 X 0.6	21 X 0.6	21.5 X 0.6	22 X 0.6	22.5 X 0.6	23 X 0.6
23.5 X 0.6	24 X 0.6	24.5 X 0.6	25 X 0.6	25.5 X 0.6	26 X 0.6
26.5 X 0.6	27 X 0.6	27.5 X 0.6	28 X 0.6	28.5 X 0.6	29 X 0.6
29.5 X 0.6	30 X 0.6	30.5 X 0.6	31 X 0.6	31.5 X 0.6	32 X 0.6

14.5 X 0.7	15 X 0.7	15.5 X 0.7	16 X 0.7	16.5 X 0.7	17 X 0.7
17.5 X 0.7	18 X 0.7	18.5 X 0.7	19 X 0.7	19.5 X 0.7	20 X 0.7
20.5 X 0.7	21 X 0.7	21.5 X 0.7	22 X 0.7	22.5 X 0.7	23 X 0.7
23.5 X 0.7	24 X 0.7	24.5 X 0.7	25 X 0.7	25.5 X 0.7	26 X 0.7
26.5 X 0.7	27 X 0.7	27.5 X 0.7	28 X 0.7	28.5 X 0.7	29 X 0.7
29.5 X 0.7	30 X 0.7	30.5 X 0.7	31 X 0.7	31.5 X 0.7	32 X 0.7

14.5 X 0.8	15 X 0.8	15.5 X 0.8	16 X 0.8	16.5 X 0.8	17 X 0.8
17.5 X 0.8	18 X 0.8	18.5 X 0.8	19 X 0.8	19.5 X 0.8	20 X 0.8
20.5 X 0.8	21 X 0.8	21.5 X 0.8	22 X 0.8	22.5 X 0.8	23 X 0.8
23.5 X 0.8	24 X 0.8	24.5 X 0.8	25 X 0.8	25.5 X 0.8	26 X 0.8
26.5 X 0.8	27 X 0.8	27.5 X 0.8	28 X 0.8	28.5 X 0.8	29 X 0.8
29.5 X 0.8	30 X 0.8	30.5 X 0.8	31 X 0.8	31.5 X 0.8	32 X 0.8


13.0 X 0.4	13.5 X 0.4	14.5 X 0.4
13.0 X 0.5	13.5 X 0.5	14.5 X 0.5
13.0 X 0.6	13.5 X 0.6	14.5 X 0.6



Rubber Cord



GB/T3672.1-2002		
EK NO.	C/S(mm)	C/S Tol±
M0120B	1.2	±0.25
M0150B	1.5	±0.25
M0160B	1.6	±0.35
M0178B	1.78	±0.35
M0190B	1.9	±0.35
M0200B	2	±0.35
M0240B	2.4	±0.35
M0250B	2.5	±0.35
M0262B	2.62	±0.40
M0300B	3	±0.40
M0350B	3.5	±0.40
M0400B	4	±0.40
M0450B	4.5	±0.50
M0500B	5	±0.50
M0534B	5.34	±0.50
M0550B	5.5	±0.50
M0570B	5.7	±0.50
M0600B	6.0	±0.50
M0650B	6.5	±0.70
M0699B	6.99	±0.70
M0700B	7	±0.70
M0750B	7.5	±0.70
M0800B	8	±0.70
M0840B	8.4	±0.70
M0850B	8.5	±0.70
M0900B	9	±0.70
M0950B	9.5	±0.70
M1000B	10	±0.70
M1100B	11	±0.80
M1200B	12	±0.80
M1270B	12.7	±0.80
M1300B	13	±0.80
M1400B	14	±0.80
M1500B	15	±0.80
M1600B	16	±0.80
M1700B	17	±1.00
M1800B	18	±1.00
M1900B	19	±1.00
M2000B	20	±1.00
M2100B	21	±1.00
M2200B	22	±1.00
M2300B	23	±1.00
M2400B	24	±1.00
M2500B	25	±1.00
Other Size Available		



Rubber Cord is mainly used to seal the large equipment such as doors, windows, etc. or stick together to form O-ring of any ID.

- Note:** 1. Products with circular, rectangular, stellar and hollow cross section is available.
2. Star(Quad) cross section more than 1.78mm is available.(Quad-ring with the C/S≥1.78mm is available)

●Circular rubber cord (NBR, 70 Shore A, Black; Silicone 70 Shore A, Black; FKM 75 Shore A, Black) has stock available.